

Total Flat Inverter Fan-Coil Bi2 SL SMART INVERTER		SL Smart Inverter 200	SL Smart Inverter 400	SL Smart Inverter 600	SL Smart Inverter 800	SL Smart Inverter 1000
ΨΥΞΗ θερμ. νερού in 7° out 12° C, θερμ. δωμ. 27° C	kW	0,83	1,76	2,56	3,3	3,81
Water Flow Rate	l/h	142	302	446	573	655
Water Pressure Loss	kPa	13,1	8,2	19	18,7	18,2
ΘΕΡΜΑΝΣΗ (50° C) θερμ. νερού in 50° C, θερμ. δωμ. 20° C	kW	0,98	2,15	2,89	3,82	4,35
Water Flow Rate (50° C)	l/h	84	185	249	329	374
Water Pressure Loss (50° C)	kPa	4,72	2,94	5,57	4,49	4,23
ΘΕΡΜΑΝΣΗ (70° C) θερμ. νερού in 70° out 60° C, θερμ. δωμ. 20° C	kW	1,77	3,88	5,21	6,88	7,83
Water Flow Rate (70° C)	l/h	152	334	448	592	673
Water Pressure Loss (70° C)	kPa	10,9	7	14,3	12,7	12,5
ΠΑΡΟΧΗ ΑΕΡΑ max-min	m³/h	160-100	320-170	460-180	575-370	650-420
Sound Power max-min Lw	dB(A)	52-38	53-39	53-41	53-42	54-42
Sound Pressure	dB(A)	34	36	37	35	38
Είσοδος / Εξοδος νερού	inches	Eurokonus 3/4	Eurokonus 3/4	Eurokonus 3/4	Eurokonus 3/4	Eurokonus 3/4
Χωρητικότητα Στοιχείου	l	0,47	0,8	1,13	1,46	1,8
Απορροφούμενη Ισχύς max-min	W	11-5	19-6	20-7	24-8	27-9
Παροχή	V/ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
ΜΗΚΟΣ	mm	759	969	1159	1359	1559
ΥΨΟΣ (χωρίς πέλματα)	mm	579	579	579	579	579
ΠΑΧΟΣ	mm	129	129	129	129	129
ΒΑΡΟΣ	kg	13	15	17	20	24
ΧΡΩΜΑ ΛΕΥΚΟ	Κωδικός	01634	01635	01636	01637	01638