



INFORMATION SHEET FOR AIR CONDITIONERS, EXCEPT DOUBLE DUCTS AND SINGLE DUCTS⁽⁵⁾

As by Commission Communication in the framework of ecodesign requirements for air conditioners and comfort fans (EU Regulation no. 206/2012) and of energy labelling of air conditioners - (EU Regulation no. 626/2011)

MODEL : GREENSTYLE PLUS 24000 UE / GREENSTYLE PLUS 24000 UI

Function to which information applies				If information applies to heating: heating season to which information relates.			
Cooling		Y		Heating (Average)(-10°C)		Y	
Heating		Y		Heating (Warmer)(+2°C)		Y	
				Heating (Colder)(-22°C)		N	
Item	symbol	value	unit	Item	symbol	value	unit
Design load				Seasonal efficiency			
Cooling	P _{designc}	6,7	kW	Cooling	SEER	6,53	-
Heating (Average)(-10°C)	P _{designh}	5,7	kW	Heating (Average)(-10°C)	SCOP (A)	4,09	-
Heating (Warmer)(+2°C)	P _{designh}	7,0	kW	Heating (Warmer)(+2°C)	SCOP (W)	5,27	-
Heating (Colder)(-22°C)	P _{designh}	-	kW	Heating (Colder)(-22°C)	SCOP (C)	-	-
Declared capacity (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature T_j				Declared Energy efficiency ratio (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature T_j			
T _j = 35°C	P _{dc}	6,46	kW	T _j = 35°C	EER _d	2,99	-
T _j = 30°C	P _{dc}	4,47	kW	T _j = 30°C	EER _d	4,99	-
T _j = 25°C	P _{dc}	2,98	kW	T _j = 25°C	EER _d	7,29	-
T _j = 20°C	P _{dc}	1,73	kW	T _j = 20°C	EER _d	13,45	-
Declared capacity (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature T_j				Declared Coefficient of Performance (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature T_j			
T _j = -7°C	P _{dh}	4,74	kW	T _j = -7°C	COP _d	2,56	-
T _j = 2°C	P _{dh}	2,89	kW	T _j = 2°C	COP _d	4,14	-
T _j = 7°C	P _{dh}	2,18	kW	T _j = 7°C	COP _d	5,25	-
T _j = 12°C	P _{dh}	1,79	kW	T _j = 12°C	COP _d	6,32	-
T _j = bivalent temperature	P _{dh}	4,74	kW	T _j = bivalent temperature	COP _d	2,56	-
T _j = operating limit temperature	P _{dh}	5,31	kW	T _j = operating limit temperature	COP _d	2,18	-
Declared capacity (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature T_j				Declared Coefficient of Performance (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature T_j			
T _j = 2°C	P _{dh}	6,86	kW	T _j = 2°C	COP _d	2,55	-
T _j = 7°C	P _{dh}	4,14	kW	T _j = 7°C	COP _d	4,67	-
T _j = 12°C	P _{dh}	2,15	kW	T _j = 12°C	COP _d	6,64	-
T _j = bivalent temperature	P _{dh}	6,86	kW	T _j = bivalent temperature	COP _d	2,55	-
T _j = operating limit temperature	P _{dh}	6,86	kW	T _j = operating limit temperature	COP _d	2,55	-
Declared capacity (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature T_j				Declared Coefficient of Performance (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature T_j			
T _j = -7°C	P _{dh}	-	kW	T _j = -7°C	COP _d	-	-
T _j = 2°C	P _{dh}	-	kW	T _j = 2°C	COP _d	-	-
T _j = 7°C	P _{dh}	-	kW	T _j = 7°C	COP _d	-	-
T _j = 12°C	P _{dh}	-	kW	T _j = 12°C	COP _d	-	-
T _j = bivalent temperature	P _{dh}	-	kW	T _j = bivalent temperature	COP _d	-	-
T _j = operating limit temperature	P _{dh}	-	kW	T _j = operating limit temperature	COP _d	-	-
T _j = -15°C	P _{dh}	-	kW	T _j = -15°C	COP _d	-	-
Bivalent temperature				Operating limit temperature			
Heating (Average)	T _{biv}	-7	°C	Heating (Average)	T _{ol}	-10	°C
Heating (Warmer)	T _{biv}	2	°C	Heating (Warmer)	T _{ol}	2	°C
Heating (Colder)	T _{biv}	-	°C	Heating (Colder)	T _{ol}	-	°C
Power consumption of cycling				Efficiency of cycling			
Cooling	P _{cycc}	-	kW	Cooling	EER _{cyc}	-	-
Heating	P _{cyh}	-	kW	Heating	COP _{cyc}	-	-
Degradation coefficient cooling(**)	C _{dc}	0,25	-	Degradation coefficient heating(**)	C _{dh}	0,25	-
Electric power input in power modes other than "active mode"				Seasonal electricity consumption			
Off mode	P _{OFF}	-	W	Cooling	Q _{CE}	359	kWh/a
Standby mode	P _{SB}	0,6	W	Heating (Average)(-10°C)	Q _{HE/A}	1950	kWh/a
Thermostat-off mode	P _{TO}	51,4/13,0	W	Heating (Warmer)(+2°C)	Q _{HE/W}	1859	kWh/a
Crankcase heater mode	P _{CK}	-	W	Heating (Colder)(-22°C)	Q _{HE/C}	-	kWh/a
Capacity control type				Other items			
Fixed		N		Sound power level (indoor/outdoor)	L _{WA}	63/66	dB(A)
Staged		N		Refrigerant type		R32	
Variable		Y		Global warming potential	GWP	675	KgCO ₂ eq.
				Rated air flow (indoor/outdoor)		1300	m ³ /h
For more detailed information				ARGOCLIMA SPA - Via A. Varo,35 - Alfianello (BS) - ITALY - www.argoclima.com			

(5) For multisplit appliances, data shall be provided at a Capacity ratio of 1.

(**) If default Cd= 0,25 is chosen, then results from cycling tests are not required. Otherwise either the heating or cooling cycling test value is required



Product Fiche

Model: GREENSTYLE PLUS 24000 UE / GREENSTYLE PLUS 24000 UI

Manufacturer : ARGOClima SPA - via Alfeno Varo, 35 - Alfianello (BS) – Italy;

Sound power level (indoor unit / outdoor unit): 63 / 66 dB(A);

Refrigerant: R32

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling mode

SEER: 6,5

Energy efficiency class: A++

P_{designc}: 6,7 kW

Annual electricity consumption **359** kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode

Climate type: Average (-10°C) / Warmer (+2°C)

SCOP: 4,1/5,2/-

Energy efficiency class: A+/A+++/A-

P_{designh}: 5,7/7,0/- kW

The back up heating capacity for SCOP calculation: # kW.

Annual electricity consumption **1950/1859/-** kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.